

Scissor Lift



Model	Unit	TM-K3662	TM-K2380	TM-K4580	TM-K32100	TM-K23118
Lifting Capacity	(kg)	360	230	450	320	230
Maximum Platform Occupancy	(persons)	2	2	2	2	2
Lifting Capacity - Extension Deck	(kg)	113	113	113	113	113
Max. Working Height	(mm)	8200	10000	10000	12000	13800
Max. Platform Height	A (mm)	6200	8000	8000	10000	11800
Min. Platform Height	B (mm)	1040	1160	1160	1290	1410
Platform Length-stowed	C (mm)	2270	2270	2270	2270	2270
Platform Length-extended	(mm)	3180	3180	3180	3180	3180
Slide-out Platform Extension Deck	(mm)	910	910	910	910	910
Platform Width-outside	D (mm)	810	810	1150	1150	1150
Guardrail Height	(mm)	1100	1100	1100	1100	1100
Toeboard Height	(mm)	150	150	150	150	150
Height-stowed: Rails Raised	E (mm)	2140	2260	2260	2390	2510
Rails Folded	(mm)	1810	1930	1860	1990	2110
Length-stowed	F (mm)	2450	2450	2450	2450	2450
Length-stowed Extended	(mm)	3360	3360	3360	3360	3360
Width	G (mm)	810	810	1170	1170	1170
Wheelbase	H (mm)	1870	1870	1870	1870	1870
Ground Clearance-center	I (mm)	100	100	100	100	100
With Pothole Guards Deployed	J (mm)	19	19	19	19	19
Driving Height		Full Height				
Driving Speed-stowed	(km/h)	3.5	3.5	3.5	3.5	3.5
Drive Speed-raised	(km/h)	0.8	0.8	0.8	0.8	0.8
Gradeability-stowed	(%)	25%	25%	25%	25%	25%
Turning Radius	(mm)	2100	2100	2200	2200	2200
Raise/lower speed	(sec)	32/35	32/35	32/35	32/35	32/35
Controls		Proportional				
Drive		Dual front wheel				
Multiple Disc Brakes		Dual rear wheel				
Tires - solid non-marking	(mm)	381×127	381×127	381×127	381×127	381×127
Storage Battery	(V/Ah)	24V DC (4×6V 225AH)	24V DC (4×6V 225AH)	24V DC (4×6V 225AH)	24V DC (4×6V 240AH)	24V DC (4×12V 300AH)
Power Source	(V/kw)	24V/3kw	24V/3kw	24V/3kw	24V/3kw	24V/4.5kw
Charger	(V/A)	24V/25A	24V/25A	24V/25A	24V/25A	24V/30A
Hydraulic System Capacity	(L)	16	16	16	16	16
Weight	(kg)	1900	2060	2320	2550	2840